According to the European Regulation (EC) No. 1907/2006, Commission Regulation (EC) No. 453/2010

Product name: Dexoll 15W-40 A3/B4

Date of issue: 19. 05. 2015

Revision date: 28. 11. 2016 (Version 1.1)

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY

1.1 Product Identifier

Dexoll 15W-40 A3/B4

Chemical name:

Mixtures

Registration No.:

None

Index No.:

None

1.2 Relevant identified uses of the substance/mixture and uses advised against

Motor oil

1.3 Details of the supplier of the safety data sheet

Name: GrandX, s.r.o

Place of business: Železničná 3214/1, 038 61 Vrútky

Phone: +421 434 306 414
E-mail: info@grandx.sk
Website: www.grandx.sk

1.4 Emergency phone numbers

National Toxicological Information Center +421 2 54 77 4 166

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance/mixture

According to 1272/2008 (CLP) the product is classified as hazardous.

Harmful for the aquatic life: Aquatic Chronic 3, H412

2.2 Label elements according to the European Regulation (EC) No 1272/2008

Pictogram: none

Warning description: none Standard phrases of hazard:

Harmful to aquatic life with long lasting effects

Safe handling instructions

Avoid release to the environment

Dispose of contents/container according to local regulations

Hazardous components which must be listed on the label

Contains calcium sulfonate. May produce an allergic reaction.

Other requirements

None

2.3 Other hazards

The product is not persistent, bioaccumulative and toxic chemical substance or very persistent and very bioaccumulative chemical substance according to the criteria set out in Annex XIII to the EC (PBT, vPvB). Flammable liquid: Prolonged or frequently repeated exposure to this product may cause eye and skin irritation. The inhalation of oil mist may irritate the breathing passages. Swallowing and subsequent vomiting may make the liquid reach and seriously damage the lungs.

According to the European Regulation (EC) No. 1907/2006, Commission Regulation (EC) No. 453/2010

Product name: Dexoll 15W-40 A3/B4

Date of issue: 19. 05. 2015

Revision date: 28. 11. 2016 (Version 1.1)

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

The product is not the substances

3.2 Mixtures

Substance name	Substance content in the product (%)	EC No.	CAS No.	Classification according to 1272/2008 (CLP)	Reg. No.
Amines, polyethylenepoly-, reaction products with 1,3-dioxolan-2-one and succinic anhydride monopolyisobutenyl derivs.	2.50	604-611-9	147880-09-9	Aquatic Chronic 4, H413	not available
Benzenesulfonic acid, methyl-, mono-C20-24- branched alkyl derivs., calcium salts	0.50	-	722503-68-6	Aquatic Chronic 4, H413 Skin Sens. 1, H317	not available
Phenol, dodecyl-, branched	0.15	310-154-3	121158-58-5	Skin Corr. 1C, H314 Eye Irrit. 2, H319 Repr. 1B, H360 Aquatic Acute 1, H400, M=10 Aquatic Chronic 1, H410, M=10	01-2119513207-49
*Mineral (base) oils	Exposure limits see Article 8.1.				01-2119486951-26

^{*}The base, highly refined mineral oils used in these products contain less than 3 % of the DMSO extract according to IP 346. Within the intention of note L in the list of classified products, they are not classified as dangerous substances.

Full texts of H-phrases are quoted in Section 16

Further information

For the exposure limits stipulated by the Scientific Committee on Occupational Exposure Limits, see Section 8.1.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures

If the first aid treatment is to be administered, release tight clothing and keep the exposed person warm and at rest. If conscious, place the exposed person to the stabilised position and get prompt medical attention. In case of cardiac arrest, apply cardiac massage and call medical assistance immediately. If unconscious but breathing, place the exposed person to the stabilised position and call medical assistance immediately.

The first aid instructions are structured according to separate exposure ways:

Inhalation: Move the exposed person to fresh air or to a well-ventilated place, keep the exposed person warm and at rest, do not leave the person unattended. Get prompt medical assistance.

Skin contact: Remove the contaminated clothes and footwear immediately. Keep washing the affected body parts with soap and warm water and treat them with a suitable cream. If any irritation, swelling or reddening occurs, get prompt medical assistance. Wash the contaminated clothes before re-use. Footwear and other leather clothing parts must be replaced with new.

Contact with eyes: Check for contact lenses and remove them, if present. Rinse the eyes thoroughly with ample quantity of clean (lukewarm, if possible) water for at least 15 minutes. If eye irritation persists, seek medical assistance.

Ingestion: Remove any artificial denture, if present. Rinse the mouth with water, but never induce vomiting - vomit should not get into the lungs. Get prompt medical attention. If nevertheless spontaneous vomiting occurs, place the exposed person to the stabilised position with his/her legs slightly elevated. Seek immediate medical assistance.

4.2 Most important symptoms and effects, both acute and delayed

None

According to the European Regulation (EC) No. 1907/2006, Commission Regulation (EC) No. 453/2010

Product name: Dexoll 15W-40 A3/B4

Date of issue: 19. 05. 2015

Revision date: 28. 11. 2016 (Version 1.1)

4.3 Indication of any immediate medical attention and special treatment needed

Inhalation: The product has negative effects on the central nervous system. At higher concentrations, the product vapours have narcotic effects that may cause convulsions or even death. Check for breathing and pulse rate of the affected person.

Ingestion and inhalation: If swallowed or inhaled, the product may cause serious damage of lungs. Do not induce vomiting. Contraindications: induced vomiting and gastric irrigation. Administration of medicinal charcoal has no effect. The affected person must be monitored at least for the period of 48 to 72 hours. Monitoring for pulmonary oedema symptoms starts six hours after the ingestion/inhalation and it continues at least for the period of 48 to 72 hours.

SECTION 5: FIRE FIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing means: Heavy, medium and light air-mechanical foam, type B or C fire-extinguishing powders.

Unsuitable extinguishing means: Water jet (for cooling only).

5.2 Special hazards arising from substance or mixture

Combustion products and hazardous gases: smoke, carbon monoxide, carbon dioxide. Explosive mixtures with air are formed.

5.3 Advice for firefighters

Fire-fighting teams exposed to smoke or vapours must wear respiratory and eye protection. In confined spaces, the teams must use a self-contained breathing apparatus.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Prevent any contamination of clothing/footwear with the product; prevent any contact with skin and eyes. Use suitable protective clothing; if contaminated, change the clothing immediately. Remove any potential source of ignition. Strictly no smoking or naked flames. If possible, larger spills may be covered with foam in order to control the creation of vapours and aerosols. Provide for good ventilation of the affected areas. All persons not taking part in rescue operations must be kept away to a sufficient distance.

6.2 Environmental precautions

Act as quick as possible, do not allow to enter drains, underground water or watercourses and soil by enclosing the affected area (damming, closing of gulleys). Notify the relevant authorities.

6.3 Methods and material for containment and cleaning up

If possible, contain the spillage and pump off or remove the product mechanically or draw it off the water surface. Let absorb any residual or smaller quantities to a suitable sorbent (Vapex, Chezacarb, saw dust, sand) and place it into labelled containers for further disposal in accordance with the relevant waste disposal legislation.

6.4 References to other sections

Apart from the instruction set out in this Section, other important information is shown in section 8 - EX-POSURE CONTROLS AND SECTION 13 - DISPOSAL CONSIDERATIONS.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling

The premises must be equipped according to the requirements of ČSN 75 3415 (Czech Standard). All fire-safety measures must be followed while handling the product. Strictly no smoking or naked flames. In addition, it is necessary to avoid any inhalation of vapours or aerosol, contamination of skin and/or eyes. If handling of heavy containers is necessary, use suitable handling equipment and avoid of any possibility of slipping. Do not eat, drink and smoke at work. Store the product away from foodstuffs, drinks and fodder.

7.2 Conditions for safe storage, including any incompatibilities

The provisions of ČSN 65 0201 are applicable for the product storage. Store the product only in tightly-closed vessels/containers purported for gasoline storage and placed at a well-ventilated place, away from any ignition sources and possible penetration of water/mechanical impurities. Protect against static dis-

According to the European Regulation (EC) No. 1907/2006, Commission Regulation (EC) No. 453/2010

Product name: Dexoll 15W-40 A3/B4

Date of issue: 19. 05. 2015

Revision date: 28. 11. 2016 (Version 1.1)

charge. All power and lighting installations must be constructed according to the relevant regulations. Strictly no smoking.

7.3 Specific end use(s)

Motor oil

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTIVE EQUIPMENT

8.1 Control parameters

Workplace occupational exposure limit (under Regulation No. 361/2007 Coll., as amended):

PEL mineral oil: 5 mg/m³ NPK-P mineral oil: 10 mg/m³

Inhalation: long-term exposure: occupational DNEL (inhalation) intermittent = $5.4 \text{ mg/m}^3/8 \text{ h}$

general population DNEL (inhalation) intermittent = 1.2 mg/m³/24 h

8.2 Exposure controls

Observe general safety and hygienic measures; do not eat, drink and smoke at work. After washing the skin with warm water and soap, treat it preventively with a regeneration cream.

Eye/face protection: Use protective goggles or safety eyewear (face shield).

Skin protection: Use protective gloves resistant against oil products and tested according to EN 374; best of all made of nitrile or neoprene rubber.

Respiratory protection: Not necessary, if the vapour concentration in air is less than the concentration limits. If the opposite is the case or aerosols are created, use emergency escape mask with A, AX (brown) filters or any other mask types suitable of protecting against organic gases and vapours.

Thermal hazard: None

Environmental exposure controls: It is necessary to prevent leakage into the environment by all available means.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance: liquid

Colour: yellow to brown

Odour: typical

Odour threshold value: not determined

pH: no determination necessary

Pour point: -27 °C

Initial boiling point and boiling range: not determined

Flash point OK: > 210 °C

Vaporisation rate: not determined

Flammability: IV. Class

Upper/lower explosion or flammability limits: not determined

Vapour pressure: < 10 Pa at 20 °C
Vapour density: not determined
Relative density: 868 kg/m³ at 15 °C
Solubility: insoluble in water

Separation factor: n-octanol/water: not determined

Self-ignition temperature: > 350 °C

Decomposition temperature: not determined

Viscosity: 12.5 to 16.3 mm²/s/100 °C

Explosive properties: not explosive Oxidation properties: not oxidising

According to the European Regulation (EC) No. 1907/2006, Commission Regulation (EC) No. 453/2010

Product name: Dexoll 15W-40 A3/B4

Date of issue: 19. 05. 2015

Revision date: 28. 11. 2016 (Version 1.1)

9.2 Other information

Combustion point: > 235 °C

SECTION 10: STABILITY & REACTIVITY

10.1 Reactivity: No reactivity danger exists.

- 10.2 Chemical stability: Stable under recommended storage and handling conditions.
- 10.3 Possibility of dangerous reactions: No dangerous reactions are possible.
- **10.4 Conditions to be avoided:** Creation of concentrations within the explosion limits, presence of ignition sources and contact with a naked flame.
- 10.5 Incompatible materials: Strong oxidisers.
- **10.6 Hazardous decomposition products:** Under normal conditions: none; if burning under deficiency of air, carbon monoxide may be formed.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity: oral toxicity (rat) $LD_{50} > 5~000$ mg/kg (OECD 401)

dermal toxicity (rabbit) $LD_{50} > 2~000~mg/kg$ (OECD 402) inhalation toxicity (rabbit) $LC_{50} > 5~000~mg/m^3$ (OECD 403)

Chronic toxicity: chronic inhalation toxicity NOAEC > 220 mg/m³ (OECD 412) **Skin corrosion/irritation:** OECD 404 test results proved no the skin irritation. **Serious eye damage/irritation:** OECD 405 test results proved no eye irritation.

Respiratory or skin sensitization: the respiratory organ sensitisation data are missing, but no such sensitisation is expected. As regards the sensitisation by skin contact, OECD 406 tests were made and no sensitisation proved.

Germ cell mutagenicity: data is missing

Carcinogenicity: Carcinogenic activity induced by repeated dermal irritation can be avoided by minimizing contact with the skin.

Reproduction toxicity: data is missing.

STOT – single exposure: not determined

STOT – repeated exposure: not determined

Aspiration hazards: None.

SECTION 12: ECOLOGICAL INFORMATION

Based on acute toxicity of invertebrates and algae, the product is classified as toxic to the environment, H412.

12.1 Toxicity

Acute toxicity for aquatic environment: fish - LL_{50} (96 hrs) > 100 mg/l, NOEL \geq 100 mg/l (OECD 203) algae EL_{50} (72 hrs) \geq 100 mg/l (OECD 201) invertebrates EL_{50} (48 hrs) > 10 000 mg/l, NOEL \geq 1000 mg/l (OECD 202)

Chronic toxicity for aquatic environment: invertebrates NOEL (21 days) 10 mg/l, fish NOEL (21 days) 10 mg/l Toxicity for soil microorganisms and for soil macroorganisms: none

- 12.2 Persistence and degradability: Not expected the substance is not soluble in water.
- **12.3 Bioaccumulative potential:** Not expected the substance is biodegradable.
- 12.4 Mobility in soil: Not expected the substance is biodegradable.
- 12.5 Results of PBT and vPvB assessment: Not expected because of the composition and low solubility in water.
- 12.6 Other adverse effects: The formation of product layers on water surfaces prevents the access of oxygen.

According to the European Regulation (EC) No. 1907/2006, Commission Regulation (EC) No. 453/2010

Product name: Dexoll 15W-40 A3/B4

Date of issue: 19. 05. 2015

Revision date: 28. 11. 2016 (Version 1.1)

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Substance disposal procedures: Waste, impaired product or unused/surplus product must be handed over to the person authorised for waste disposal according to the provisions of Act No. 185/2001 Coll., on Waste, as amended later, for the purposes of further use or disposal (according to the manufacturer's recommendations).

Waste code: N 13 02 05, in sorbent: N 15 02 02

Contaminated packaging disposal procedures: The containers with product residua must be placed on the place specified by the municipal authorities or handed over to the person authorised for waste disposal

Waste legislation: Act No. 185/2001 Coll., on Waste, as amended later and connected implementation rules and regulations.

SECTION 14: TRANSPORT INFORMATION

Nomenclature and labelling according to the European Agreement concerning the International Carriage of Dangerous Goods, Road (ADR)/Rail (RID)

14.1 UN Number: none

14.2 UN proper shipping name: none14.3 Transport hazard class(es): none

14.4 Packing group: none

14.5 Environmental hazard: none

14.6 Special precautions for users:

Petroleum liquids under the Act on the waters, as amended, considered dangerous because of the requirements of the quality of surface and groundwater when transporting large volumes necessary to follow the advice of Standard 75 3418.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and IBC Code: not applicable

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation special for the substance or mixture

✓ Act on Clean Air Protection, as amended later, incl. connected regulations and rules.

The product does not represent a volatile organic substance pursuant to Act on Clean Air Protection, as amended and relevant regulations of the Ministry of Environment.

- ✓ ČSN 65 0201 Flammable Liquids manufacturing, storage and handling premises According to ČSN 65 0201, the product is classified in the IV Flammability Class.
- ✓ ČSN 33 0371 In explosive electrical installation Explosive mixtures Classification and methods of testing

According to ČSN 33 077, the product is classified in the T3 Thermal Class and IIA Explosive Class.

- ✓ Government Regulation No. 361/2007 Coll., by which the conditions of occupational health and safety are stipulated, as amended later.
- ✓ ČSN 75 3415 Protection of water against oil products. Premises for oil product handling and storage.
- ✓ Act No. 350/2011 Coll., on chemical substances and chemical mixtures, and on amendments of some acts.
- ✓ Regulation (EU) No. 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)
- ✓ Regulation (EC) No. 1272/2008 on classification, labelling and packaging of substances and mixtures (CLP)

15.2 Chemical safety assessment

The chemical safety assessment has been made.

According to the European Regulation (EC) No. 1907/2006, Commission Regulation (EC) No. 453/2010

Product name: Dexoll 15W-40 A3/B4

Date of issue: 19. 05. 2015

Revision date: 28. 11. 2016 (Version 1.1)

SECTION 16: OTHER INFORMATION

16.1 List of H-phrases and P-phrases according to Regulation (EC) No. 1272/2008:

Standard safety phrases: H-phrases

H314 Causes severe skin burns and eye damage

H317 May cause an allergic skin reaction

H319 Causes serious eye irritation

H360 May damage fertility or the unborn child

H410 Very toxic to aquatic life with long lasting effects

H412 Harmful to aquatic life with long lasting effects

H413 May cause long lasting harmful effects to aquatic life

EUH208 Contains calcium sulfonate. May produce an allergic reaction

Safe handling instructions: P-phrase

P273 Avoid release to the environment

P501 Dispose of contents/container according to local regulations

16.2 Training

The user is obliged to get acquainted with the safety precautions relating to the product handling / treatment and complete applicable trainings at the workplace before he/she starts to work with the product.

16.3 Information on changes

- ✓ The change has been made on the basis of the Commission Regulation (EU) No. 453/2010 coming into
 effect.
- ✓ The change Classification CLP
- ✓ The change (version 1.1) art. 2.1, 2.2, 2.3, 3.2, 12, 14.5, 16.1, 16.2.

The data contained in this safety data sheet are based on our current knowledge and experience and they are related to the specified product only. The user is responsible for the product correct handling under the current legislation.